




**COBRA** sewer cleaning hose is engineered and manufactured to handle the toughest and most harsh conditions found in high-pressure sewer cleaning applications. Its thermoplastic composition and unique bonded construction allows for a flexible and light-weight hose, along with superior kink resistance, and improved fitting retention. The high tensile strength polyester reinforcement provides for exceptional low volumetric expansion and eliminates moisture absorption. **Cobra** also features a tough polyether-urethane cover that offers maximum resistance to cutting, abrasion, various chemicals, and fungus.

In accordance with *WASTE*C (formerly *WEMI*) specifications, **Cobra** sewer cleaning hose offers a cream colored inner tube and corresponding markings on all assembly components. **Cobra** hose cover colors conform to industry standards for maximum operating pressure ratings.


**SERIES 4625 SEWER CLEANING HOSE – 2500 PSIG WORKING PRESSURE**

 Series #    Cover Color		Nominal Size		Pressures		Min. Bend Radius Inches	Weight Per 100' (Lbs.)
		I.D. Inches	O.D. Inches	Max. W.P. PSIG	Min Burst PSIG		
4625-12	Orange	3/4	1.140	2500	6250	4.0	29.0
4625-16	Orange	1	1.445	2500	6250	6.0	38.0

**Tube:** Polyester core tube. Cream color.  
**Cover:** Orange abrasion resistant polyurethane.  
**Branding:** Black letter ink jet branding.

**Reinforcement:** Braided polyester fibers.  
**Temperatures:** -40°F. to +135°F. (-40°C. to +57°C.)


**SERIES 4630 SEWER CLEANING HOSE – 3000 PSIG WORKING PRESSURE**

 Series #    Cover Color		Nominal Size		Pressures		Min. Bend Radius Inches	Weight Per 100' (Lbs.)
		I.D. Inches	O.D. Inches	Max. W.P. PSIG	Min Burst PSIG		
4630-12	Blue	3/4	1.170	3000	7500	4.0	30.0
4630-16	Blue	1	1.470	3000	7500	8.0	46.0

**Tube:** Polyester core tube. Cream color.  
**Cover:** Blue abrasion resistant polyurethane.  
**Branding:** Black letter ink jet branding.

**Reinforcement:** Braided polyester fibers.  
**Temperatures:** -40°F. to +135°F. (-40°C. to +57°C.)

**SERIES 4640 SEWER CLEANING HOSE – 4000 PSIG WORKING PRESSURE**

 Series #    Cover Color		Nominal Size		Pressures		Min. Bend Radius Inches	Weight Per 100' (Lbs.)
		I.D. Inches	O.D. Inches	Max. W.P. PSIG	Min Burst PSIG		
4640-08	Lime Green	1/2	.85	4000	10,000	4.0	19.5

**Tube:** Polyester core tube. Cream color.  
**Cover:** Green abrasion resistant polyurethane.  
**Branding:** Black letter ink jet branding.

**Reinforcement:** Braided polyester fibers.  
**Temperatures:** -40°F. to +135°F. (-40°C. to +57°C.)

**For safety assurance, Cobra sewer cleaning hose is factory tested and sold as assemblies only.**